

(1390 REV. 5-93) US DEPT. OF COMMERCE PATENT & TRADEMARK OFFICE

ATTORNEY'S DOCKET NUMBER
111494

**TRANSMITTAL LETTER TO THE
UNITED STATES
DESIGNATED/ELECTED OFFICE
(DO/EO/US) CONCERNING A FILING
UNDER 35 U.S.C. 371**

U.S. APPLICATION NO.
(if known, sec 37 C.F.R.1.5)

10/018466

INTERNATIONAL APPLICATION NO.
PCT/JP00/06378INTERNATIONAL FILING DATE
September 19, 2000PRIORITY DATE CLAIMED
September 22, 1999TITLE OF INVENTION
ELECTRONIC CAMERAAPPLICANT(S) FOR DO/EO/US
Hideyasu KUNIBA, Sadami OKADA, Toshihisa KUROIWA

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☒ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☐ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☒ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US)
6. ☒ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☐ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☐ have not been made and will not be made.
8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)).

Items 11. to 16. below concern other document(s) or information included:

11. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☒ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☐ A FIRST preliminary amendment.
- ☐ A SECOND or SUBSEQUENT preliminary amendment.
14. ☐ A substitute specification.
15. ☐ Entitlement to small entity status is hereby asserted.
16. ☐ Other items or information:

U.S. APPLICATION NO. (if known, see 37 C.F.R. 1.5) 107018460	INTERNATIONAL APPLICATION NO. PCT/JP00/06378	ATTORNEY'S DOCKET NUMBER 111494
---	---	--

17. <input checked="" type="checkbox"/> The following fees are submitted: Basic National fee (37 CFR 1.492(a)(1)-(5)): Search Report has been prepared by the EPO or JPO\$890.00 International preliminary examination fee paid to USPTO (37 CFR 1.482)\$710.00 No international preliminary examination fee paid to USPTO (37 CFR 1.482) but international search fee paid to USPTO (37 CFR 1.445(a)(2))\$740.00 Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO\$1,040.00 International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(2)-(4)\$ 100.00	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width:50%; text-align: center;">CALCULATIONS</td> <td style="width:50%; text-align: center;">PTO USE ONLY</td> </tr> <tr> <td colspan="2" style="height: 150px; vertical-align: top;"> <div style="display: flex; justify-content: space-between;"> <div> <p>ENTER APPROPRIATE BASIC FEE AMOUNT = \$890.00</p> <p>Surcharge of \$130.00 for furnishing the oath or declaration later than <input checked="" type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(e)).</p> <table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th style="width:20%;">Claims</th> <th style="width:20%;">Number Filed</th> <th style="width:20%;">Number Extra</th> <th style="width:20%;">Rate</th> <th style="width:20%;"></th> </tr> <tr> <td>Total Claims</td> <td>7- 20 =</td> <td>0</td> <td>X \$ 18.00</td> <td>\$</td> </tr> <tr> <td>Independent Claims</td> <td>3- 3 =</td> <td>0</td> <td>X \$ 84.00</td> <td>\$</td> </tr> <tr> <td colspan="4">Multiple dependent claim(s)(if applicable)</td> <td>\$</td> </tr> <tr> <td colspan="4" style="text-align: right;">TOTAL OF ABOVE CALCULATIONS =</td> <td>\$</td> </tr> <tr> <td colspan="4">Reduction by 1/2 for filing by small entity, if applicable.</td> <td>- \$</td> </tr> <tr> <td colspan="4" style="text-align: right;">SUBTOTAL =</td> <td>\$890.00</td> </tr> <tr> <td colspan="4">Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 month from the earliest claimed priority date (37 CFR 1.492(f)).</td> <td>\$</td> </tr> <tr> <td colspan="4" style="text-align: right;">TOTAL NATIONAL FEE =</td> <td>\$890.00</td> </tr> </table></div> <div> <p>Amount to be refunded \$</p> <p>Charged \$</p> </div> </div> </td> </tr> </table>	CALCULATIONS	PTO USE ONLY	<div style="display: flex; justify-content: space-between;"> <div> <p>ENTER APPROPRIATE BASIC FEE AMOUNT = \$890.00</p> <p>Surcharge of \$130.00 for furnishing the oath or declaration later than <input checked="" type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(e)).</p> <table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th style="width:20%;">Claims</th> <th style="width:20%;">Number Filed</th> <th style="width:20%;">Number Extra</th> <th style="width:20%;">Rate</th> <th style="width:20%;"></th> </tr> <tr> <td>Total Claims</td> <td>7- 20 =</td> <td>0</td> <td>X \$ 18.00</td> <td>\$</td> </tr> <tr> <td>Independent Claims</td> <td>3- 3 =</td> <td>0</td> <td>X \$ 84.00</td> <td>\$</td> </tr> <tr> <td colspan="4">Multiple dependent claim(s)(if applicable)</td> <td>\$</td> </tr> <tr> <td colspan="4" style="text-align: right;">TOTAL OF ABOVE CALCULATIONS =</td> <td>\$</td> </tr> <tr> <td colspan="4">Reduction by 1/2 for filing by small entity, if applicable.</td> <td>- \$</td> </tr> <tr> <td colspan="4" style="text-align: right;">SUBTOTAL =</td> <td>\$890.00</td> </tr> <tr> <td colspan="4">Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 month from the earliest claimed priority date (37 CFR 1.492(f)).</td> <td>\$</td> </tr> <tr> <td colspan="4" style="text-align: right;">TOTAL NATIONAL FEE =</td> <td>\$890.00</td> </tr> </table></div> <div> <p>Amount to be refunded \$</p> <p>Charged \$</p> </div> </div>		Claims	Number Filed	Number Extra	Rate		Total Claims	7- 20 =	0	X \$ 18.00	\$	Independent Claims	3- 3 =	0	X \$ 84.00	\$	Multiple dependent claim(s)(if applicable)				\$	TOTAL OF ABOVE CALCULATIONS =				\$	Reduction by 1/2 for filing by small entity, if applicable.				- \$	SUBTOTAL =				\$890.00	Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 month from the earliest claimed priority date (37 CFR 1.492(f)).				\$	TOTAL NATIONAL FEE =				\$890.00
CALCULATIONS	PTO USE ONLY																																																	
<div style="display: flex; justify-content: space-between;"> <div> <p>ENTER APPROPRIATE BASIC FEE AMOUNT = \$890.00</p> <p>Surcharge of \$130.00 for furnishing the oath or declaration later than <input checked="" type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(e)).</p> <table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th style="width:20%;">Claims</th> <th style="width:20%;">Number Filed</th> <th style="width:20%;">Number Extra</th> <th style="width:20%;">Rate</th> <th style="width:20%;"></th> </tr> <tr> <td>Total Claims</td> <td>7- 20 =</td> <td>0</td> <td>X \$ 18.00</td> <td>\$</td> </tr> <tr> <td>Independent Claims</td> <td>3- 3 =</td> <td>0</td> <td>X \$ 84.00</td> <td>\$</td> </tr> <tr> <td colspan="4">Multiple dependent claim(s)(if applicable)</td> <td>\$</td> </tr> <tr> <td colspan="4" style="text-align: right;">TOTAL OF ABOVE CALCULATIONS =</td> <td>\$</td> </tr> <tr> <td colspan="4">Reduction by 1/2 for filing by small entity, if applicable.</td> <td>- \$</td> </tr> <tr> <td colspan="4" style="text-align: right;">SUBTOTAL =</td> <td>\$890.00</td> </tr> <tr> <td colspan="4">Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 month from the earliest claimed priority date (37 CFR 1.492(f)).</td> <td>\$</td> </tr> <tr> <td colspan="4" style="text-align: right;">TOTAL NATIONAL FEE =</td> <td>\$890.00</td> </tr> </table></div> <div> <p>Amount to be refunded \$</p> <p>Charged \$</p> </div> </div>		Claims	Number Filed	Number Extra	Rate		Total Claims	7- 20 =	0	X \$ 18.00	\$	Independent Claims	3- 3 =	0	X \$ 84.00	\$	Multiple dependent claim(s)(if applicable)				\$	TOTAL OF ABOVE CALCULATIONS =				\$	Reduction by 1/2 for filing by small entity, if applicable.				- \$	SUBTOTAL =				\$890.00	Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 month from the earliest claimed priority date (37 CFR 1.492(f)).				\$	TOTAL NATIONAL FEE =				\$890.00				
Claims	Number Filed	Number Extra	Rate																																															
Total Claims	7- 20 =	0	X \$ 18.00	\$																																														
Independent Claims	3- 3 =	0	X \$ 84.00	\$																																														
Multiple dependent claim(s)(if applicable)				\$																																														
TOTAL OF ABOVE CALCULATIONS =				\$																																														
Reduction by 1/2 for filing by small entity, if applicable.				- \$																																														
SUBTOTAL =				\$890.00																																														
Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 month from the earliest claimed priority date (37 CFR 1.492(f)).				\$																																														
TOTAL NATIONAL FEE =				\$890.00																																														

a. ☒ Check No. 126160 in the amount of \$890.00 to cover the above fees is enclosed.

b. ☐ Please charge my Deposit Account No. _____ in the amount of \$_____ to cover the above fees. A duplicate copy of this sheet is enclosed.

c. ☒ The Director is hereby authorized to charge any additional fees which may be required, or credit any overpayment, to Deposit Account No. 15-0461. A duplicate copy of this sheet is enclosed.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:
 OLIFF & BERRIDGE, PLC
 P.O. Box 19928
 Alexandria, Virginia 22320

Date: December 19, 2001

NAME: James A. Oliff
 REGISTRATION NUMBER 27,075

 NAME: Joel S. Armstrong
 REGISTRATION NUMBER: 36,430

10/018466

531 Rec'd PCT/JP 19 DEC 2001

DESCRIPTION

ELECTRONIC CAMERA

5 The disclosure of the following priority application
is herein incorporated by reference:

Japanese Patent Application No. H11- 268825 filed September
22, 1999

10 TECHNICAL FIELD

 The present invention relates to an electronic camera
that implements image compression so as to achieve a
substantially constant code volume resulting from image data
compression.

15

BACKGROUND ART

 A large volume of image data handled in an electronic
camera or a computer normally undergo image compression (e.g.,
JPEG compression) processing. The image compression
20 processing may be executed through, for instance, the
following steps 1 ~ 6.

1. The electronic camera determines a target image data
compression rate (target code volume) in correspondence to
the compressed image quality setting selected by the
25 photographer (e.g., by switching to one of;

FINE/NORMAL/BASIC).

2. The electronic camera divides the image data constituted of the brightness Y and the color differences Cb, Cr into blocks each made up of, for instance, 8 x 8 pixels.

5 The electronic camera then implements DCT (discrete cosine transform) in units of the individual blocks resulting from the division and obtains transformation coefficients each corresponding to one of 8 x 8 discrete spatial frequencies.

3. The electronic camera prepares a reference
10 quantization table defining a quantization step in correspondence to each of the 8 x 8 transformation coefficients. By multiplying data in the reference quantization table by a scale factor SF (a type of compression parameter), the electronic camera obtains a quantization
15 table to be utilized in actual processing.

4. The electronic camera quantizes each of the 8 x 8 transformation coefficients using the quantization table obtained in step 3.

5. The electronic camera encodes the DC component in the
20 quantized data in order to eliminate any redundancy while allowing for an estimated difference relative to the immediately preceding block. In addition, it implements zigzag scanning on the AC component in the quantized data and then encodes the AC component in order to eliminate any
25 redundancy.

6. If the size of the compressed file (hereafter referred to as the "compression size") deviates from the allowable target code volume range, the electronic camera first readjusts the value of the scale factor SF and then re-engages in the operation in step 3 above. If, on the other hand, the compression size is within the allowable target code volume range (normally set to; target code volume \pm allowable error), it ends the image compression processing.

Through the processing described above, the image data can be compressed at a compression rate within the allowable target compression rate range.

If the allowable target code volume range is set to a fixed range such as target code volume \pm allowable error as explained above, the compression code volume fluctuates within the allowable range. As a result, when the compressed data having undergone the image compression processing are sequentially recorded at a storage medium, there will be a significant unused area remaining on the storage medium, i.e., an area the size of which is not large enough to record the compression code volume corresponding to a single frame (hereafter referred to as a "remaining area"). While the size of the remaining area changes as of the photographing/recording operation advances due to the inconsistency in the compression code volume mentioned earlier, the average compression code volume is highly likely

to be roughly equal to the target code volume. Accordingly the remaining area does not manifest the tendency for either a steady increase or a steady decrease as the photographing/recording operation progresses.

5 In addition, the capacity of the storage medium is not always set at an integral multiple of the target code volume.

For the reasons stated above, a remaining area the size of which cannot be disregarded is often left on the storage medium. From the viewpoint of preventing any image quality
10 loss during the image compression, it is desirable to maximize the compression code volume per frame so as to leave as little remaining area as possible.

DISCLOSURE OF THE INVENTION

15 An object of the present invention is to provide an electronic camera that allows the target code volume to be exceeded as necessary when the electronic camera engages in a fixed-length compression in order to minimize the size of the remaining area.

20 In order to achieve the object described above, an electronic camera according to the present invention comprises an image-capturing element that captures an image of a subject and outputs image data of the captured subject image, a compression processing unit that implements a
25 fixed-length compression on the image data so as to compress

the image data within a specific range of a target code volume,
a recording unit that records compressed data resulting from
the compression implemented at the compression processing
unit into a storage medium, a remaining-capacity detection
5 unit that detects the remaining capacity of the storage medium,
a remaining-capacity correction unit that determines a
nominal remaining capacity by subtracting a predetermined
adjustment capacity from the remaining capacity, a remaining
frame quantity calculation unit that determines a nominal
10 remaining frame quantity by dividing the nominal remaining
capacity by the target code volume or an estimated compression
code volume ascertained based upon previous compression
results, a display unit that displays the nominal remaining
frame quantity calculated at the remaining frame quantity
15 calculation unit and an allowable upper limit setting unit
that sets an extent to which the target code volume may be
exceeded within a capacity range corresponding to the
adjustment capacity. The compression processing unit
performs a fixed-length compression on the image data while
20 allowing the target code volume to be exceeded within the
extent.

Since a portion of the capacity of the storage medium
is designated in advance as the adjustment capacity and the
target for the compression code volume can be exceeded in
25 correspondence to the adjustment capacity, it is possible to

ensure that the target is only exceeded to an appropriate extent during a fixed-length compression. Compared to a fixed-length compression, which does not allow the target for the compression code volume to be exceeded at all, the size of the final remaining area can be reduced with a high degree of efficiency. In addition, since the nominal remaining frame quantity is determined by excluding the adjustment capacity from the remaining capacity of the storage medium, the nominal remaining frame quantity is calculated to a value which is smaller by a degree corresponding to the adjustment capacity at all times. As a result, even when fluctuations in the compression code volume accumulate, for instance, an irregular change, in which the nominal remaining frame quantity becomes drastically decreased at once, can be prevented, and thus, the user is afforded worry-free operation.

The remaining-capacity correction unit may modify the adjustment capacity in correspondence to any of the remaining capacity, the previous compression results, the nominal remaining frame quantity and the remaining frame quantity determined by dividing the remaining capacity by the target code volume when calculating the nominal remaining capacity.

The electronic camera may further comprise a decision-making unit that makes a decision as to whether or not the possibility that the adjustment capacity will become

completely used up by recording compressed data with a code volume exceeding the target within the extent into the storage medium while the storage medium still has room to allow one or more frames of data to be stored exists based upon a previous
5 compression code volume tendency and a downward correction unit that makes a downward correction on the target code volume if the decision-making unit decides that there is such a possibility. In this structure, the compression processing unit implements an image data fixed-length
10 compression by using the target code volume having undergone the downward correction.

An electronic camera according to the present invention comprises an image-capturing element that captures an image of a subject and outputs image data of the captured subject
15 image, a compression processing unit that implements a fixed-length compression on the image data so as to compress the image data within a specific range of a target code volume, a recording unit that records compressed data resulting from the compression implemented at the compression processing
20 unit into a storage medium, a remaining-capacity detection unit that detects the remaining capacity of the storage medium and an allowable upper limit setting unit that sets an extent to which the target code volume may be exceeded within a capacity range corresponding to the remaining capacity. The
25 compression processing unit performs a fixed-length

compression on the image data while allowing the target code volume to be exceeded within the extent.

Since the extent to which the target for the compression code volume may be exceeded is determined in correspondence
5 to the remaining capacity, the target is allowed to be exceeded only to an appropriate extent during the fixed-length compression, thereby enabling a planned utilization of the remaining area.

The electronic camera further comprises a decision-
10 making unit that makes a decision as to whether or not the possibility that the capacity corresponding to the remaining capacity will become completely used up by recording compressed data with a code volume exceeding the target within the extent into the storage medium while the storage medium
15 still has room to allow one or more frames of data to be stored exists based upon a tendency in previous compression results and a downward correction unit that makes a downward correction on the target code volume if the decision-making unit decides that there is such a possibility. In this
20 structure, the compression processing unit implements an image data fixed-length compression by using the target code volume having undergone the downward correction.

An electronic camera according to the present invention may alternatively comprise an image-capturing element that
25 captures an image of a subject and outputs image data of the

captured subject image, a compression processing unit that implements a fixed-length compression on the image data so as to compress the image data within a predetermined target code volume range, a recording unit that records compressed data resulting from the compression implemented at the compression processing unit into a storage medium, the remaining-capacity detection unit that detects the remaining capacity of the storage medium, an excess calculation unit that determines a value representing an excess by dividing the remaining capacity by the target code volume or an estimated compression code volume obtained based upon previous compression results and an allowable upper limit setting unit that sets an extent to which the target code volume may be exceeded within a capacity range corresponding to the excess. The compression processing unit in this electric camera performs a fixed-length compression on the image data while allowing the target code volume to be exceeded within the extent.

Since the compression code volume is allowed to exceed the target in conformance to the excess, the target can only be exceeded to an appropriate extent during the fixed-length compression, thereby enabling a planned utilization of the remaining area.

The electronic camera may further comprise a decision-making unit that makes a decision as to whether or

not the possibility that the capacity corresponding to the excess will become completely used up by recording compressed data with a code volume exceeding the target within the extent into the storage medium while the storage medium still has room to allow one or more frames of data to be stored exists based upon a tendency in previous compression results and a downward correction unit that makes a downward correction on the target code volume if the decision-making unit decides that there is such a possibility. In this structure, the compression processing unit implements an image data fixed-length compression by using the target code volume having undergone the downward correction.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic block diagram illustrating the structure adopted in an electronic camera;

FIG. 2 is a flowchart of the image compression processing implemented in a first embodiment;

FIG. 3 is a flowchart of the image compression processing implemented in a second embodiment;

FIG. 4A is a flowchart of the first half of the image compression processing implemented in a third embodiment;

FIG. 4B is a flowchart of the second half of the image compression processing implemented in the third embodiment;

and

FIG. 5 is a flowchart of the image compression processing implemented in a fourth embodiment.

THE BEST MODE FOR CARRYING OUT THE INVENTION

5 The following is an explanation of the embodiments of the present invention, given in reference to the drawings.

-First Embodiment-

FIG. 1 is a schematic block diagram illustrating the structure of an electronic camera 10. The electronic camera 10 in FIG. 1 is mounted with a photographic lens 11. An image-capturing element 13 is provided in the image space of the photographic lens 11. Image data generated at the image-capturing element 13 sequentially undergo specific types of processing at a signal processing unit 15, an A/D conversion unit 16 and an image processing unit 17, and then are input to a compression processing unit 18 as digital image data. The compression processing unit 18 performs JPEG compression on the input image data and outputs compressed data to a recording unit 19. The recording unit 19 records the input compressed image data to a storage medium 20 which may be a memory card.

The electronic camera 10 also includes a control unit 21 for implementing system control, an operating button group 24 and a display unit 25. The operating button group 24 is operated by the user to perform camera operations and to set

the image quality of compressed image data. The number of remaining frames and the like are displayed at the display unit 25.

FIG. 2 is a flowchart of the image compression

5 processing implemented at the compression processing unit 18.

The following is an explanation of the image compression

processing which characterizes the present invention, given

in reference to FIG. 2. In step S0, the control unit 21 sets

the adjustment capacity for adjusting the extent to which the

10 compression code volume is allowed to exceed the target to

an initial value. In addition, the control unit 21 determines

an allowable upper limit to the target code volume in

correspondence to the adjustment capacity set at the initial

value. At this time, the allowable range for the target code

15 volume should be set equal to or higher than (target code

volume - allowable error) and equal to or lower than (target

code volume + capacity corresponding to adjustment

capacity).

In step S1, the control unit 21 engages in communication

20 with the recording unit 19 and obtains the remaining capacity

of the storage medium 20.

In step S2, the control unit 21 subtracts the

predetermined adjustment capacity from the remaining

capacity that has been obtained and thus calculates a nominal

25 remaining capacity. The control unit 21 also divides the

calculated nominal remaining capacity by the target code volume and thus determines a nominal remaining frame quantity.

In step S3, the control unit 21 makes a decision as to
5 whether or not the nominal remaining frame quantity is equal to or higher than 2. If a negative decision is made, i.e., if it is decided that the nominal remaining frame quantity is equal to or smaller than 1, the control unit 21 judges that the storage capacity of the storage medium 20 is to be depleted
10 soon and the operation proceeds to step S4. If, on the other hand, an affirmative decision is made, i.e., if it is decided that the nominal remaining frame quantity is equal to or larger than 2, the control unit 21 judges that the storage medium 20 still has available storage area and the operation
15 proceeds to step S7.

In step S4, the control unit 21 makes a decision as to whether or not the remaining capacity of the storage medium 20 exceeds a predetermined minimum recording capacity. If the remaining capacity is lower than the minimum recording
20 capacity and those a negative decision is made, the control unit 21 judges that the current target compression rate does not allow for enough space to store compressed data at the storage medium 20, before the operation proceeds to step S5. If, on the other hand, the remaining capacity exceeds the
25 minimum recording capacity and thus an affirmative decision

is made, the control unit 21 judges that the storage medium 20 still has enough space to store compressed corresponding to one frame, and the operation proceeds to step S6.

It is to be noted that the minimum recording capacity
5 may be set at the allowable upper limit of the target code volume (set without taking into consideration the adjustment capacity). In addition, it may be set to the allowable lower limit to the target code volume. Alternatively, the minimum recording capacity may be set independently of the conditions
10 for ending the fixed-length compression processing.

In step S5, the control unit 21 issues a warning prompting a replacement of the recording medium 20 by indicating the nominal remaining frame quantity as "0" at the display unit 25. The control unit 21 temporarily stops the
15 photographing operation and the like in this state and waits in standby until the user replaces the storage medium 20.

In step S6, the control unit 21 sets the nominal remaining frame quantity to "1". The control unit 21 also sets the allowable upper limit to the target code volume equal
20 to the remaining capacity to achieve maximum efficiency in utilizing the final remaining area.

In step S7, the control unit 21 indicates the nominal remaining frame quantity at the display unit 25 of the electronic camera 10.

25 In step S8, the control unit 21 remains in standby for

an image capturing operation by the user and executes an image capturing processing once the image capturing operation is performed by the user. It is to be noted that if the setting for the target compression rate (target code volume) is
5 changed while the control unit 21 is in standby, the control unit 21 returns to step S1 to reset the nominal remaining frame quantity.

In step S9, the control unit 21 issues an instruction to perform an image compression to the compression processing
10 unit 18. The compression processing unit 18 executes an image compression on image data obtained through the image capturing operation.

In step S10, the control unit 21 makes a decision as to whether not the file size of the compressed data resulting
15 from the image compression is within the allowable range for the target code volume. If the file size is outside the allowable range and thus, a negative decision is made, the control unit 21 proceeds to step S11. If the file size is within the allowable range and an affirmative decision is made,
20 on the other hand, the control unit 21 proceeds to step S12.

In step S11, the control unit 21 makes an adjustment by either increasing or decreasing the scale factor in reference to the compression results and then returns to step S9.

25 In step S12, the control unit 21 issues an instruction

to record the compressed data to the recording unit 19. In response, the recording unit 19 records the compressed data at the storage medium 20. Once the recording processing is completed, the control unit 21 returns to step S1 to standby
5 for a photographing operation for the next frame.

Through the sequence of processing explained above, the nominal remaining frame quantity is calculated and the fixed-length compression is executed by taking into consideration the adjustment capacity.

10 To summarize the actions and advantages achieved in the first embodiment, the control unit 21 sets aside in advance a portion of the storage capacity of the storage medium 20 as the adjustment capacity and allows the compression code volume to exceed the target during the image compression
15 within a capacity range corresponding to the secured adjustment capacity. The allowable target code volume range is equal to or higher than (target code volume - allowable error) and equal to or lower than (target code volume + capacity corresponding to adjustment capacity). In this
20 situation, when the image compression is implemented on image data with a large image information volume the compression code volume of which is bound to be relatively large, the compression code volume is allowed to exceed the target as necessary by prioritizing the utilization of the remaining
25 area. As a result, the remaining area can be reliably reduced

while preventing any loss of image quality resulting from the compression as appropriate.

In addition, the nominal remaining frame quantity is calculated (step S2) smaller in consideration of the adjustment capacity by subtracting the adjustment capacity from the remaining capacity of the storage medium 20 in the first embodiment and, thus, worrisome situations for the user such as a drastic decrease in the number of remaining frames at the indicator during an operation can be prevented.

Furthermore, a decision is made as to whether or not the number of remaining frames over which image data can be recorded at the storage medium 20 is 1 (step S4) and the allowable upper limit to the target code volume is set equal to the remaining capacity when the number of remaining frames reaches 1 (step S6) in the first embodiment. As a result, compressed data resulting from the fixed-length compression, the size of which is very close to the remaining capacity, are allowed to be recorded, thereby making it possible to effectively reduce the remaining area in the storage medium 20.

It is to be noted that while an explanation is given above in reference to the first embodiment on an example in which the adjustment capacity is fixed, the adjustment capacity does not need to be fixed. For instance, the adjustment capacity may be changed in correspondence to the

remaining capacity, the results of a previous compression or the number of remaining frames (the number of frames calculated without taking into consideration the adjustment capacity).

5 Alternatively, the adjustment capacity may be adjusted in the following manner. Under normal circumstances, the remaining area, which is used up as the remaining capacity and the remaining frame quantity decrease at the storage medium, is assumed to become smaller over time, since the capacity corresponding to the adjustment capacity is larger
10 than the allowable error. Namely, when the allowable target code volume is set equal to or higher than (target code volume - allowable error) and equal to or lower than (target code volume + capacity corresponding to adjustment capacity), the
15 range above the target code volume is bound to be wide and thus the size of the data having undergone the compression processing is likely to be larger than the target code volume. Accordingly, by gradually reducing the adjustment capacity as the remaining capacity or the remaining frame quantity
20 decreases, a planned utilization of the remaining area up to the very last frame is enabled.

 In addition, the control unit 21 may adjust the adjustment capacity to a larger value if the extent to which the previous compression code volume exceeded the target has
25 been larger than expected. In this case, an even more smaller

value is set for the nominal remaining frame quantity to further ensure that an irregular change such as a drastic reduction in the nominal remaining frame quantity is prevented.

5 The control unit 21 may adjust the adjustment capacity to a larger value if the previous compression code volume is smaller than the target code volume and a large remaining area is expected to be left unused, instead. In this case, the remaining area can be used up more efficiently by allowing
10 the compression code volume to exceed the target to a further extent.

It is to be noted that while the nominal remaining frame quantity is calculated by dividing the nominal remaining capacity by the target code volume in the first embodiment,
15 the present invention is not limited to this example. For instance, the nominal remaining frame quantity may be calculated by dividing the nominal remaining capacity by an estimated compression code volume value ascertained based upon previous compression results.

20 -Second Embodiment-

FIG. 3 presents a flowchart of the image compression processing implemented at the control unit 21 in the second embodiment. It is to be noted that since the electronic camera is structured identically to that in the first
25 embodiment (see FIG. 1), its explanation is omitted. In step

S31 in FIG. 3, the control unit 21 engages in communication with the recording unit 19 and obtains the remaining capacity at the storage medium 20.

In step S32, the control unit 21 determines the
5 remaining frame quantity and the excess by dividing the remaining capacity that has been obtained by the target code volume.

In step S33, the control unit 21 makes a decision as
to whether or not the remaining frame quantity is equal to
10 or larger than 2. If the remaining frame quantity is equal to or larger than 2 and thus an affirmative decision is made, the control unit 21 proceeds to step S34. If, on the other hand, the remaining frame quantity is 1 or 0 and a negative decision is made, the control unit 21 and proceeds to step
15 S35.

In step S34, the control unit 21 calculates an allowable upper limit by adding the target code volume to a value obtained by multiplying the excess by a predetermined factor before the operation proceeds to step S7. It is to be noted
20 that since the processing in steps S7 ~ S12 is identical to the processing in FIG. 2 implemented in the first embodiment, its explanation is omitted.

In step S35, the control unit 21 makes a decision as
to whether or not the remaining capacity of the storage medium
25 20 exceeds a predetermined minimum recording capacity. If

the remaining capacity is lower than the minimum recording capacity and thus a negative decision is made, the control unit 21 judges that the current target compression rate does not allow for enough space to store compressed data at the storage medium 20, before the operation proceeds to step S36. If, on the other hand, the remaining capacity exceeds the minimum recording capacity and thus an affirmative decision is made, the control unit 21 judges that the storage medium 20 still has enough space to store compressed data corresponding to one frame, and the operation proceeds to step S37.

In step S36, the control unit 21 indicates the remaining frame quantity "0" at the display unit 25 and temporarily halts the image capturing operation and the like after issuing a warning to prompt replacement of the storage medium 20.

In step S37, the control unit 21 sets the remaining frame quantity to "1". The control unit 21 also sets the allowable upper limit to the target code volume equal to the remaining capacity to achieve maximum efficiency in utilizing the final remaining area. Then, the control unit 21 proceeds to step S7. Since the processing implemented in step S7 and subsequent steps is identical to the processing in the first embodiment explained earlier, its explanation is omitted.

Through the sequence of processing explained above, the fixed-length compression is executed by allowing for a change

occurring in the excess (the estimated capacity value representing the remaining area).

To summarize the actions and advantages achieved in the second embodiment, the control unit 21 determines the remaining frame quantity and the excess by dividing the remaining capacity at the storage medium 20 by the target code volume and dynamically adjusts the allowable upper limit to the target code volume as long as there is still ample remaining capacity. As a result, the compression code volume is allowed to exceed the target over an appropriate deviation range in correspondence to the estimated capacity value representing the remaining area assumed to remain unused at the storage medium 20 in the end and thus, the final remaining area can be used up sufficiently and appropriately to leave a minimal area left unused during the fixed-length compression. In particular, since the compression code volume resulting from an image compression on image data with a large image information volume tends to exceed the target to an appropriate degree, the extent of the loss of image quality resulting from the compression is lessened to a desirable degree.

Since the allowable upper limit can be lowered when the remaining capacity has decreased and there is no longer any margin left, the remaining area can be utilized in a more economical manner in such a case to ensure that the remaining

area is not used up while the operation is still in progress.

In addition, the formula described in reference to step S34 is utilized to calculate the allowable upper limit in the second embodiment. Since any excess data beyond the target
5 code volume corresponding to the current frame are stored by utilizing only a portion of the excess, the remaining excess can be left for storing data overflow from subsequent frames.

It is to be noted that the formula used to calculate the allowable upper limit for utilizing a portion of the
10 excess is not limited to that used in step S34. Generally speaking, any capacity value smaller than the excess can be allocated for the allowable upper limit. For instance, the allowable upper limit may be calculated by adding the target code volume to a value obtained by dividing the excess by the
15 remaining frame quantity.

-Third Embodiment-

FIGS. 4A and 4B present a flowchart of the image compression processing implemented at the control unit 21 in the third embodiment. It is to be noted that since the
20 electronic camera is structured identically to that in FIG. 1, its explanation is omitted. In step S41 in FIG. 4A, the control unit 21 engages in communication with the recording unit 19 and obtains the remaining capacity at the storage medium 20.

25 In step S42, the control unit 21 makes a decision as

to whether or not there are any compressed data obtained through a photographing operation performed at the same target compression rate within an immediately preceding specific length of time. If a negative decision is made, i.e.,
5 if no such compressed data are present, the control unit 21 proceeds to step S43. If, on the hand, an affirmative decision is made that compressed data are present, the control unit 21 proceeds to step S44.

In step S43, the control unit 21 determines the
10 remaining frame quantity and the excess by dividing the remaining capacity by the target code volume and then the operation proceeds to step S33. It is to be noted that since the processing in steps S33 ~ S37 and in steps S7 ~ S12 is identical to the processing in FIG. 3 implemented in the
15 second embodiment, its explanation is omitted.

In step S44, the control unit 21 obtains the compression code volumes of the compressed data generated during the immediately preceding predetermined length of time. The control unit 21 then eliminates any extreme values among the
20 compression code volumes thus obtained and averages the remaining compression code volumes to use as an estimated compression code volume value.

In step S45, the control unit 21 determines the remaining frame quantity and the excess by dividing the
25 remaining capacity by the estimated value.

In step S46, the control unit 21 makes an estimate as to whether or not there is a possibility of the remaining area (the excess, to be more specific) at the storage medium 20 being used up while the operation is in progress by projecting the change in the excess over the remaining frames based upon the change having occurred over the most recent predetermined number of frames.

If an affirmative decision is made in step S47 that there is a possibility of the remaining area being used up while the operation is in progress, the control unit 21 proceeds to step S48. If, on the other hand, a negative decision is made that there is no possibility of the remaining area being used up for the time being, the control unit 21 proceeds to step S33 in FIG. 4B. It is to be noted that since the processing in step S33 and subsequent steps is identical to the processing in the second embodiment, its explanation is omitted.

In step S48, the control unit 21 makes a downward correction on the target code volume so as to ensure that the remaining area is not used up while the operation is in progress in an attempt to restore the remaining area. Then, the control unit 21 proceeds to step S33 in FIG. 4B. Since the processing in step S33 and subsequent steps is identical to the processing implemented in the second embodiment explained earlier, its explanation is omitted.

Through the sequence of processing explained above, the fixed-length compression is executed by taking into consideration changes occurring in the excess (referred to as the estimated capacity value representing the remaining area) ascertained by dividing the remaining capacity by the target code volume or by the estimated value for the compression code volume.

To summarize the actions and advantages achieved in the third embodiment, the control unit 21 allows the compression code volume to exceed the target over an appropriate deviation range in correspondence to the utilization status of the remaining area during the fixed-length compression as in the second embodiment and, as a result, it becomes possible to reduce the ultimate remaining area in an appropriate and sufficient degree.

In particular, by ascertaining an estimated compression code volume value based upon the compression code volumes of compressed data generated during the immediately preceding predetermined length of time (step S44), dividing the remaining capacity at the storage medium 20 by the estimated value to determine the remaining frame quantity and the excess (step S45) and projecting the change in the excess over the remaining frames based upon the change have occurred over the most recent predetermined number of frames (step S46), the possibility of the remaining area of the storage medium

20 being used up while the operation is in progress is gauged. If the remaining area becomes small, the need to greatly narrow the allowable target code volume range for the fixed-length compression arises. When the allowable range
5 is narrowed under such circumstances, the frequency with which the scale factor has to be adjusted increases, which may result in a delay in the completion of the fixed-length compression. However, by gauging the possibility of the remaining area becoming used up halfway as in the third
10 embodiment, a downward correction can be made on the target code volume if, for instance, the target is exceeded frequently resulting in a drastic reduction in the remaining area (step S48). As a result, the remaining area can be restored on the storage medium 20. Consequently, the
15 remaining area is not used up halfway and thus, any increase in the length of time required for the fixed-length compression processing is prevented.

-Fourth Embodiment-

FIG. 5 presents a flowchart of the image compression
20 processing implemented at the control unit 21 in the fourth embodiment. Since the image compression processing in the embodiment is achieved by adding steps S13 and S14 to the processing in the flowchart in FIG. 2 achieved in the first embodiment, an explanation is given by focusing on the
25 processing implemented and these two steps. It is to be noted

that the electronic camera assumes a structure identical to that shown in FIG. 1 and thus, its explanation is omitted.

After the recording unit 19 records compressed data into the storage medium 20 in step S12, the control unit 21
5 proceeds to step S13.

In step S13, the control unit 21 modifies the adjustment capacity in correspondence to the file size of the compressed data that have been recorded immediately before.

In step S14, the control unit 21 modifies the allowable
10 upper limit to the target code volume in correspondence to the modified adjustment capacity. After the modification processing, the control unit 21 returns to step S1 and stands by for the photographing operation for the next frame.

Through the sequence of processing explained above, the
15 nominal remaining frame quantity is calculated and the fixed-length compression is executed by taking into consideration the adjustment capacity.

To summarize the actions and advantages achieved in the fourth embodiment, the control unit 21 sets aside in advance
20 a portion of the storage capacity of the storage medium 20 as the adjustment capacity and allows the compression code volume to exceed the target during the image compression within a capacity range corresponding to the secured adjustment capacity, thereby achieving a reduction in the
25 ultimate remaining area, as in the first embodiment.

In addition, the nominal remaining frame quantity is calculated (step S2) smaller in consideration of the adjustment capacity by subtracting the adjustment capacity from the remaining capacity of the storage medium 20 and, thus, worrisome situations for the user such as a drastic decrease in the number of remaining frames at the indicator during an operation can be prevented.

Furthermore, a decision is made as to whether or not the number of remaining frames over which image data can be recorded at the storage medium 20 is 1 (step S4) and the allowable upper limit to the target code volume is set equal to the remaining capacity when the number of remaining frames reaches 1 (step S6) in the fourth embodiment. As a result, compressed data resulting from the fixed-length compression, the size of which is very close to the remaining capacity, are allowed to be recorded, thereby making it possible to effectively reduce the remaining area in the storage medium 20.

Moreover, the control unit 21 modifies the adjustment capacity in correspondence to the file size of the compressed data having been recorded immediately before (step S13) and modifies the allowable upper limit to the target code volume in conformance to the modified adjustment capacity (step S14). Thus, when the file size is very large (small) and the target code volume is exceeded (not exceeded) to result in a decrease

(increase) of the remaining area, for instance, an appropriate and sufficient reduction in the ultimate remaining area can be achieved by making a downward (upward) correction on the allowable upper limit to the target code
5 volume.

It is to be noted that while the adjustment capacity is modified in correspondence to the file size of the compressed data having been recorded immediately before, the adjustment capacity may be adjusted in correspondence to the
10 results of one or more previous compressions, the remaining capacity or the remaining frame quantity. Under normal circumstances, the remaining area is assumed to be used up and become smaller over time, as the remaining capacity and the remaining frame quantity decrease at the storage medium
15 20. Accordingly, the control unit 21 gradually reduces the adjustment capacity as the remaining capacity or the remaining frame quantity decreases to achieve a planned utilization to use up the remaining area up to the very last frame.

20 In addition, the control unit 21 may adjust the adjustment capacity to a larger value if the extent to which the previous compression code volume exceeded the target has been larger than expected. In this case, an even more smaller value is set for the nominal remaining frame quantity to
25 further ensure that an irregular change in the nominal

remaining frame quantity is prevented.

As an alternative, the control unit 21 may adjust the adjustment capacity to a larger value if the previous compression code volume is smaller than the target code volume and a large remaining area is expected to be left unused as well. In this case, the remaining area can be used up more efficiently by allowing the compression code volume to exceed the target to a further extent.

It is to be noted that while the nominal remaining frame quantity is calculated by dividing the nominal remaining capacity by the target code volume in the fourth embodiment, the present invention is not limited to this example. For instance, the nominal remaining frame quantity may be calculated by dividing the nominal remaining capacity by an estimated compression code volume value ascertained based upon previous compression results.

INDUSTRIAL APPLICABILITY

While an explanation is given above on an example in which the present invention is adopted in conjunction with an electronic camera which stores compressed image data at a detachable storage medium such as a memory card, the present invention may also be adopted in an electronic camera which stores image data in an internal memory. In addition, the present invention may be adopted in a PDA (personal digital

assistant) as well as in electronic cameras. Furthermore,
 while an explanation is given above on an example in which
 the present invention is adopted in an electronic camera which
 implements JPEG compression on image data, the present
 5 invention may also be adopted in an electronic camera that
 implements MPEG compression for dynamic images.

CLAIMS

1. An electronic camera comprising:

an image-capturing element that captures an image of
a subject and outputs image data of the captured subject
5 image;

a compression processing unit that implements a
fixed-length compression on the image data so as to compress
the image data within a specific range of a target code volume;

a recording unit that records compressed data resulting
10 from the compression implemented at said compression
processing unit into a storage medium;

a remaining-capacity detection unit that detects a
remaining capacity of the storage medium;

a remaining-capacity correction unit that determines
15 a nominal remaining capacity by subtracting a predetermined
adjustment capacity from the remaining capacity;

a remaining frame quantity calculation unit that
determines a nominal remaining frame quantity by dividing
said nominal remaining capacity by the target code volume or
20 an estimated compression code volume ascertained based upon
previous compression results;

a display unit that displays said nominal remaining
frame quantity calculated at said remaining frame quantity
calculation unit; and

25 an allowable upper limit setting unit that sets an

extent to which said target code volume may be exceeded within a capacity range corresponding to said adjustment capacity, wherein:

5 said compression processing unit performs a fixed-length compression on the image data while allowing said target code volume to be exceeded within said extent.

2. An electronic camera according to claim 1, wherein:

10 said remaining-capacity correction unit modifies said adjustment capacity in correspondence to any of the remaining capacity, previous compression results, said nominal remaining frame quantity and a remaining frame quantity determined by dividing the remaining capacity by said target code volume, to calculate said nominal remaining capacity.

15

3. An electronic camera according to claim 1, further comprising:

20 a decision-making unit that makes a decision as to whether or not a possibility of said adjustment capacity becoming completely used up by recording compressed data, which exceeds the target code volume within said extent, into the storage medium exists while the storage medium still has room to allow frames of data to be stored, based upon a previous compression code volume tendency; and

25 a downward correction unit that makes a downward

correction on said target code volume if said decision-making unit decides that there is such a possibility, wherein:

said compression processing unit implements a fixed-length compression on the image data by using said
5 target code volume having undergone downward correction.

4. An electronic camera comprising:

an image-capturing element that captures an image of a subject and outputs image data of the captured subject
10 image;

a compression processing unit that implements a fixed-length compression on the image data so as to compress the image data within a specific range of a target code volume;

a recording unit that records compressed data resulting
15 from the compression implemented at said compression processing unit into a storage medium;

a remaining-capacity detection unit that detects a remaining capacity of the storage medium; and

an allowable upper limit setting unit that sets an
20 extent to which said target code volume may be exceeded within a capacity range corresponding to said remaining capacity, wherein:

said compression processing unit performs fixed-length compression on the image data while allowing said target code
25 volume to be exceeded within said extent.

5. An electronic camera according to claim 4, further comprising:

a decision-making unit that makes a decision as to
5 whether or not a possibility of a capacity corresponding to
the remaining capacity becoming completely used up by
recording compressed data, which exceeds the target code
volume within said extent, into the storage medium exists
while the storage medium still has room to allow frames of
10 data to be stored, based upon a previous compression code
volume tendency; and

a downward correction unit that makes a downward
correction on said target code volume if said decision-making
unit decides that there is such a possibility, wherein:

15 said compression processing unit implements a
fixed-length compression on the image data by using said
target code volume having undergone downward correction.

6. An electronic camera comprising:

20 an image-capturing element that captures an image of
a subject and outputs image data of the captured subject
image;

a compression processing unit that implements a
fixed-length compression on the image data so as to compress
25 the image data within a specific range of a target code volume;

a recording unit that records compressed data resulting from the compression implemented at said compression processing unit into a storage medium;

a remaining-capacity detection unit that detects a
5 remaining capacity of the storage medium;

an excess calculation unit that determines a value representing an excess by dividing the remaining capacity by said target code volume or an estimated compression code volume obtained based upon previous compression results; and
10 an allowable upper limit setting unit that sets an extent to which said target code volume may be exceeded within a capacity range corresponding to said excess, wherein:

said compression processing unit performs a fixed-length compression on the image data while allowing said
15 target code volume to be exceeded within said extent.

7. An electronic camera according to claim 6, further comprising:

a decision-making unit that makes a decision as to
20 whether or not a possibility of a capacity corresponding to said excess becoming completely used up by recording compressed data, which exceeds the target code volume within said extent, into the storage medium exists while the storage medium still has room to allow frames of data to be stored,
25 based upon a previous compression code volume tendency; and

a downward correction unit that makes a downward correction on said target code volume if said decision-making unit decides that there is such a possibility, wherein:

said compression processing unit implements a
5 fixed-length compression on the image data by using said target code volume having undergone downward correction.

FIG. 1




FIG.2




FIG.3




FIG.4A




FIG.4B





FIG.5



DECLARATION AND POWER OF ATTORNEY
FOR PCT APPLICATION FOR UNITED STATES

As a below named inventor, I hereby declare that:
my residence, post office address and citizenship are as stated below next to my name;

I verily believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: ELECTRONIC CAMERA

described and claimed in the specification:

Check one

- * a. ☒ attached hereto.
- b. ☐ filed on _____ as Application Serial No.

This application discloses and claims subject matter disclosed in my or our earlier filed pending application, International Application No. PCT/JP00/06378, filed September 19, 2000.

I have reviewed and understand the contents of this application, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose to the Office all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations §1.56.

Under Title 35, U.S. Code §119, the priority benefits of the following foreign application(s) filed by me or my legal representatives or assigns within one year prior to said international application are hereby claimed:
Japanese Patent Application No. 11-268825 filed September 22, 1999

The following application(s) for patent or inventor's certificate on this invention were filed in countries foreign to the United States of America either (a) more than one year prior to said international application, or (b) before the filing date of the above-named foreign priority application(s)

As to any and all subject matter of this application which is not common to said earlier application, I acknowledge the duty to disclose to the Office all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, §1.56, which became available between the filing date of the international application and the filing date of this application.

Under Title 35, U.S. Code §119, the priority benefits of the following foreign application(s) filed by me or my legal representatives or assigns within one year prior to this application are hereby claimed:

The following application(s) for patent or inventor's certificate on such subject matter were filed in countries foreign to the United States of America either (a) more than one year prior to this application, or (b) before the filing of the above-named foreign priority application(s):

I hereby appoint the following as my attorneys of record with full power of substitution and revocation to prosecute this application and to transact all business in the Patent Office:

James A. Oliff, Reg. No. 27,075; William P. Berridge, Reg. No. 30,024;
Kirk M. Hudson, Reg. No. 27,562; Thomas J. Pardini, Reg. No. 30,411;
Edward P. Walker, Reg. No. 31,450; Robert A. Miller, Reg. No. 32,771;
Mario A. Costantino, Reg. No. 33,565; Caroline D. Dennison, Reg. No. 34,494;
and Stephen J. Roe, Reg. No. 34,463.

ALL CORRESPONDENCE IN CONNECTION WITH THIS APPLICATION SHOULD BE SENT TO OLIFF & BERRIDGE, PLC, P.O. BOX 19928, ALEXANDRIA, VIRGINIA 22320, TELEPHONE (703) 836-6400.

I hereby declare that I have reviewed and understand the contents of this Declaration, and that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

1 **Typewritten Full Name of Sole or First Inventor** 1 - ∞ Hideyasu KUNIBA
Given Name Middle Initial Family Name

2 **Inventor's Signature** 岡田 英久

3 **Date of Signature** Dec. 10 2001
Month Day Year

Residence: Shinjyuku-ku Tokyo JPY JAPAN
City State or Province Country

Citizenship: Japan

Post Office Address: C/O Nikon Corporation, 2-3, Marunouchi 3-chome, Chiyoda-ku,
(Insert complete mailing address, including country) TOKYO 100-8331 JAPAN

1 **Typewritten Full Name of Joint Inventor** 2 - ∞ Sadami OKADA
Given Name Middle Initial Family Name

2 **Inventor's Signature:** 岡田 貞子

3 **Date of Signature:** Dec. 10 2001
Month Day Year

Residence: Sakado-shi JPY Saitama Japan
City State or Province Country

Citizenship: Japan

Post Office Address: C/O Nikon Corporation, 2-3, Marunouchi 3-chome, Chiyoda-ku,
(Insert complete mailing address, including country) TOKYO 100-8331 JAPAN

1 **Typewritten Full Name of Joint Inventor** 3 - ∞ Toshihisa KUROIWA
Given Name Middle Initial Family Name

2 **Inventor's Signature:** 黒 岩 寿久

3 **Date of Signature:** Dec 13 2001
Month Day Year

Residence: Miura-shi JPY Kanagawa-ken JAPAN
City State or Province Country

Citizenship: Japan

Post Office Address: C/O Nikon Corporation, 2-3, Marunouchi 3-chome, Chiyoda-ku,
(Insert complete mailing address, including country) TOKYO 100-8331 JAPAN

1 **Typewritten Full Name of Joint Inventor** _____
Given Name Middle Initial Family Name

2 **Inventor's Signature:** _____

3 **Date of Signature:** _____
Month Day Year

Residence: _____
City State or Province Country

Citizenship: _____

Post Office Address: _____
(Insert complete mailing address, including country)

*If Box a. is checked, this form may be executed only when attached to the specification (including claims) at the end thereof. This form may be executed only when attached to the first page of the Declaration and Power of Attorney of the application to which it pertains.
Note to Inventor: Please sign name on line 2 exactly as it appears in line 1 and insert the actual date of signing on line 3.